SQP110 series

Introduction

SQP110 series (Square Plastic 110 series) is a dynamic digital signage with an 11-inch monitor. It is designed to display slideshows made of images and videos. This device is built in an USB port and a SD card slot for connection to storage devices used for storing slideshow files. SQP110 series can be used for any application that requires showing information and messages, such as advertising.

SQP110 series comes in two models, SQP110T with a touchscreen and SQP110P with a non-touch screen. With the touchscreen, users can interactively access the information displayed on the screen. The device is available in black or white color.

SQP110 series support content management system CMS Lite for remote slideshows and firmware upgrade. An additional USB to RJ-45 cable is required to allow the SQP 110 series connect to the network.

Key Features

- 11-inch touch / non-touch panel (800 × 480 ;16 :10)
- Multimedia support
- SD card and USB storage
- Network access
- Content management system CMS Lite
- Automatic slideshow display with multiple transition effects
- IR remote control
- Built-in speakers

CMS

**CMS Server**   **CMS Lite**

Authoring Tool

Clip Design   **Content Schedule**

SPECIFICATIONS

Model	SQP110 series
Panel Size (inch)	11" touch (SQP110T) 11" non-touch (SQP110P)
Aspect Ratio	16:10
Pixel Pitch (mm)	0.1 x 0.3
Video Format	Multimedia Support
Audio Format	Multimedia Support
Photo Format	JPEG, PNG
Color	262 K
Contrast	250 :1
Brightness (cd/㎡)	380
Response Time (Tr / Tf)	30 / 50 ms
View Angle (H / V)	125 ° / 105 °
Video System	NTSC / PAL
SD Slot	SD Card (FAT32 Format)
USB	Type A, USB 2.0 Backward Compatible (FAT32 Format)
Speaker	2 W x 2
Power Consumption	40 W
IR Remote Control	Yes
OSD	Yes
Function Keys	Yes
Housing	Black / White
Storage Temperature	0 °C ~ 60 °C (32 °F ~ 140°F)
Storage Humidity	5 % ~ 95 %
Operating Temperature	0 °C ~ 40 °C (32 °F ~ 104 >°F)
Operating Humidity	20 % ~ 80 %
Dimension (W x H x D)	292 x 186 x 46 mm (11.5 x 7.3 x 1.8 inch)
Net Weight	1.5 kg (3.3 lb)

Note: Specifications are subject to change without notice.

Overview

Accessory

Name	Details
  USB to RJ-45 cable	**You can use the USB to RJ-45 cable to connect the SQP110 series to the CMS Lite for remotely uploading media files or firmware to the SQP110 series.**

Packing List

- SQP110 device × 1
- AC/DC adapter × 1
- IR remote control × 1
- Software CD × 1
- Magnetic rear rack × 1